



CAPICORDA PER FUNI DI ACCIAIO



TIPO APERTO



TIPO APERTO

| TIPO CHIUSO | o max | A | B | C | D | E | F | Portata | Peso |
|-------------|---------------|-----|-----|-----|------|------|-----|---------|------|
| | funne | | | | | | | | |
| | pollici | mm | mm | mm | mm | mm | mm | Kg | Kg |
| | 1/4 | 13 | 51 | 45 | 20 | 108 | 37 | 0,9 | 0,2 |
| | 3/6 | 16 | 51 | 52 | 23 | 118 | 43 | 2,2 | 0,5 |
| | 1/2 | 22 | 64 | 57 | 26 | 140 | 54 | 4,1 | 0,7 |
| | 5/8 | 25 | 76 | 64 | 31 | 162 | 66 | 6,4 | 1,4 |
| | 3/4 | 32 | 89 | 76 | 36 | 194 | 76 | 8,5 | 2 |
| | 7/8 | 38 | 101 | 89 | 42 | 225 | 92 | 11,5 | 3,2 |
| | 1 | 44 | 114 | 102 | 52 | 254 | 100 | 15 | 5 |
| | 1,1/8 | 51 | 127 | 114 | 58 | 282 | 111 | 18,7 | 7,2 |
| | 1,3/8 | 57 | 140 | 127 | 65 | 313 | 127 | 29 | 10 |
| | 1,1/2 | 64 | 162 | 152 | 77 | 362 | 142 | 34 | 12 |
| | 1,5/8 | 70 | 165 | 165 | 80 | 393 | 152 | 37,7 | 16,3 |
| | TOTALE APERTO | 1/4 | 39 | 51 | 17 | 17,5 | 109 | 8 | 0,9 |
| | 3/8 | 44 | 51 | 20 | 20,6 | 118 | 11 | 2,2 | 0,6 |
| | 1/2 | 51 | 64 | 27 | 25,5 | 141 | 12 | 4,1 | 1,1 |
| | 5/8 | 65 | 76 | 33 | 30,2 | 171 | 14 | 6,4 | 1,7 |
| | 3/4 | 77 | 89 | 38 | 35 | 202 | 16 | 8,5 | 2,8 |
| | 7/8 | 91 | 101 | 45 | 41,3 | 235 | 19 | 11,5 | 4,6 |
| | 1 | 102 | 114 | 54 | 50,8 | 268 | 20 | 15 | 7,3 |
| | 1,1/8 | 118 | 127 | 60 | 57,1 | 300 | 21 | 18,7 | 10 |
| | 1,3/8 | 129 | 140 | 68 | 63,5 | 335 | 26 | 29 | 14,5 |
| | 1,1/2 | 154 | 152 | 76 | 69 | 334 | 30 | 34 | 20,8 |
| | 1,5/8 | 165 | 165 | 86 | 75 | 413 | 33 | 37,7 | 24,9 |