

FUNI 8 SIG - 8 FIG - 8 WIS
DI ACCIAIO COMPATTATE
a 8 trefoli anima a trefoli paralleli

8 SIG (ZINCATA)

Utilizzi:
ACCIAIERIE
AUTOGRU
CARTIERE
GRU PORTUALI
PARANCHI
STRALLI PER GRU



255 fili
 8x19 SR
 + anima metallica parallela
 trefoli compattati
 crociata destra
 crociata sinistra
 Resistenza 2160 N/mm²

Diametro fune (mm)	Diametro fili esterni (mm)	Peso per metro (kg)	Carico rottura minimo	
			(kN)	(kg)
6,2	0,45	0,169	36,4	3713
6,4	0,45	0,193	41,8	4260
7,2	0,50	0,240	51,6	5260
8,0	0,55	0,292	63,7	6400
9,0	0,60	0,360	76,8	7830
10,0	0,67	0,462	98,5	10047
11,0	0,75	0,560	126,4	12893
12,0	0,83	0,675	145,0	14790

8 FIG (ZINCATA)

303 fili
 8x25 FW
 + anima metallica parallela
 crociata destra
 crociata sinistra
 Resistenza 2160 N/mm²

Diametro fune (mm)	Diametro fili esterni (mm)	Peso per metro (kg)	Carico rottura minimo	
			(kN)	(kg)
13,0	0,70	0,77	166,0	16930
14,0	0,75	0,90	195,0	19890
15,0	0,80	1,03	222,0	22640
16,0	0,85	1,17	254,0	25900
18,0	0,97	1,48	321,0	32740
19,0	1,00	1,62	348,0	35500
20,0	1,07	1,82	397,0	40500
22,0	1,17	2,22	484,0	49360
24,0	1,30	2,64	568,0	57930

8 WIS (ZINCATA)

399 fili
 8x36 WS
 + anima metallica parallela
 crociata destra
 crociata sinistra
 Resistenza 2160 N/mm²

	Diametro fune (mm)	Diametro fili esterni (mm)	Peso per metro (kg)	Carico rottura minimo	
				(kN)	(kg)
	25,0	1,20	2,91	622,0	63440
	26,0	1,23	3,12	668,0	68130
	28,0	1,33	3,63	768,0	78340
	29,0	1,37	3,86	819,0	83540
	32,0	1,53	4,75	1009,0	102920
	34,0	1,60	5,30	1120,0	114240
	36,0	1,70	5,96	1250,0	127500
	38,0	1,80	6,65	1400,0	142800
	40,0	1,90	7,36	1550,0	158100
	42,0	2,00	8,12	1710,0	174420
	45,0	2,13	9,35	1960,0	199920
	48,0	2,27	10,64	2230,0	227460
	51,0	2,40	11,91	2515,0	256500
	54,0	2,55	13,45	2810,0	286600
	58,0	2,73	15,52	3240,0	330480
	60,0	2,85	16,70	3485,0	354400
	64,0	2,70	18,82	3930,0	400800
	67,0	2,83	20,67	4320,0	440600
	71,0	3,00	23,15	4735,0	482900
	74,0	3,13	25,30	5175,0	527800
	77,0	3,25	27,24	5530,0	564000
	82,0	3,47	31,00	6165,0	628800

487 fili
 8x47 WS
 + anima metallica parallela
 crociata destra
 crociata sinistra
 Resistenza 2160 N/mm²