

**TIPO «FAL 114 AT»****Impiego:**

Grù, argani, paranchi

**Esecuzione:**

Acciaio lucido R180

Acciaio zincato R180

Diametro fune mm.	Diametro fili esterni mm.	Peso per mt. gr.	Carico di rottura min. garantito Kg.
3	0,19	33	500
4	0,26	55	950
5	0,32	90	1.500
6	0,39	130	2.250
7	0,56	181	3.100
8	0,64	236	4.000
9	0,72	300	5.100
10	0,80	368	6.300
11	0,88	446	7.600
12	0,96	529	9.100
14	0,90	730	12.400
16	1,03	950	16.000
18	1,16	1.210	20.300
20	1,29	1.500	25.000

**TIPO «FAL 114 A.T. AS» R160**

Diametro fune mm.	Diametro fili esterni mm.	Peso per mt. gr.	Carico di rottura min. garantito
9	0,73	302	4.195
10	0,80	373	4.870
11	0,88	451	5.940
12	0,96	540	7.940
13	1,04	640	8.310

TIPO SEALE «FAL 114 A.T.» R160

Diametro fune mm.	Diametro fili esterni mm.	Peso per mt. gr.	Carico di rottura min. garantito
9	0,60	280	3.500
10	0,65	348	4.150
11	0,73	421	5.150
12	0,80	501	6.150
13	0,86	589	7.150